Bi-O Filius sauna heater

Wall heater with evaporator

Recommended for the family sauna

Outer casing:	Anthracite pearl effect
Inner casing:	Bright polished stainless steel
Evaporator filing quantity:	approx. 2 l
Stone filling:	8 kg inc.


Stainless steel herb bowl to accommodate herbs, essential oils and essences.
Integrated dry-running protection with acoustic low water signal.

Dimensions in mm	Height:	750 with 180 mm ground clearance
	Width:	470
	Depth:	240




CE IP x4
MADE IN GERMANY


Connection diagram




Sensor installation



Installation dimensions



Minimum clearances



Art.No.	Power acc. DIN	Evaporator power	Electr. connection	Fuse protection in A	for cabin volumes	Minimum dimension for ventilation and bleeding	Connection mains - control unit	Connection control unit - heater	Power switchgear required	to be used with the control units
94.5144	4,5 kW	1,0 kW	3N AC 50 Hz 400 V	3 x 16	4 - 6 m³	35 x 5 cm	5 x 2,5²	1pcs. 5 x 1,5² 1pcs 4 x 1,5²	no	ECON H1 ECON H2 EMOTEC HCS9003 EMOTEC HCS9003 DB/DL/DLF EmoTouch II PB/AF/GF
94.5145	6,0 kW	1,5 kW			6 - 8 m³					
94.5146	7,5 kW				7 - 10 m³					

All information on cable cross-sections are minimum cross-sections in mm² copper line.

Subject to technical changes

DruckNr.: 29344365en 07.12

EOS Saunatechnik GmbH
D-35759 Driedorf
Telephone (0 27 75) 82-0, Fax (0 27 75) 8 24 31